



FEATURES

- Acquire and track 65 satellites simultaneously
- Venus 6 simultaneous time-frequency search bins
- Signal detection better than -160dBm
- Reacquisition sensitivity -155dBm
- Cold start < 30 seconds at -147dBm
- Hot start < 1sec under open sky
- 5m CEP accuracy
- Support A-GPS function
- SBAS (WAAS, EGNOS) support
- USB version 2.0 interface
- Easy-plug-in Notebook
- Easy-installation USB driver
- Super mini size: 73.5x27x10 mm

GT-730F Fast Acquisition high-Sensitivity 65 Channels USB GPS Receiver Dongle

The GT-730F is a single board of USB-GPS receiver and compact all-in-one GPS module solution intended for a broad range of Original Equipment Manufacturer (OEM) products, where fast and easy system integration and minimal development risk is required.

The GT-730F is optimized for good performance and low cost. Its 65 parallel channels and Venus 6 search bins provide short start-up time and fast signal acquisition. Having fast time-to-first-fix and high sensitivity, the GT-730F offers good navigation performance even in urban canyons.

Satellite-based augmentation systems, such as WAAS and EGNOS, are supported to yield improved accuracy. Besides it also supports A-GPS function and fixed in the short time.

USB interface are provided on the interface connector. Supply voltage of 3.8V~8.0V is supported.

TECHNICAL SPECIFICATIONS

Receiver Type	65 parallel channels, L1 C/A code
Accuracy	Position 5m CEP Velocity 0.1m/sec
Startup Time (average)	< 1sec hot start < 30sec cold start
Signal Reacquisition	1s
Sensitivity	-155dBm Re-acquisition -160dBm tracking -147dBm Cold Start
Update Rate	1Hz standard
Dynamics	4G (39.2m/sec ²)
Operational Limits	Altitude < 18,000m or velocity < 515m/s (COCOM limit, either may be exceeded but not both)
Protocol	NMEA-0183 V3.01 GPGGA, GPGLL, GPGSA, GPGSV, GPRMC, GPVTG, GPZDA 4800/9600/19200/38400 baud, 8, N, 1 (The baudrate of production is 38400)
Datum	Default WGS-84 User definable
Input Voltage	3.8~8V DC
Power Consumption	< 30mA (Tracking)
Dimension	73.5mm L x 27mm W x 10mm H
Weight:	18g
Operating Temperature	-40°C ~ +85°C
Humidity	5% ~ 95%

Binary Messages

See *Binary Message Protocol User's Guide* for detailed descriptions.

CanMore Electronics Co., LTD.

No. 40, Chenggong 5th St., Jhubei City, Hsinchu County, 302, Taiwan

Phone +886 3 6586046

Fax +886 3 6583940

Email: sales@canmore.com.tw

Website: [http:// www.canmore.com.tw](http://www.canmore.com.tw)

<http://canmorecorp.trustpass.alibaba.com/>

© 2000 CanMore Electronics Co., Ltd. All rights reserved.

Not to be reproduced in whole or part for any purpose without written permission of CanMore Electronics Co., Ltd. ("CMEC")
Information provided by CMEC is believed to be accurate and reliable. These materials are provided by CMEC as a service to its customers and may be used for informational purposes only. CMEC assumes no responsibility for errors or omissions in these materials, nor for its use. CMEC reserves the right to change specification at any time without notice.

These materials are provides "as is" without warranty of any kind, either expressed or implied, relating to sale and/or use of CMEC products including liability or warranties relating to fitness for a particular purpose, consequential or incidental damages, merchantability, or infringement of any patent, copyright or other intellectual property right. CMEC further does not warrant the accuracy or completeness of the information, text, graphics or other items contained within these materials. CMEC shall not be liable for any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of these materials.

CMEC products are not intended for use in medical, life-support devices, or applications involving potential risk of death, personal injury, or severe property damage in case of failure of the product.